



TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table, Model KL-RX1



The KLYO MEDICAL SYSTEMS, INC. tables are designed to function safely with a 882 lbs (400 Kg) patient in the electro motorized model KL-RX1. All movements are soft and silent, and the table offers a longitudinal displacement of 22.44" (570 mm), to facilitate C- Arm access. The table is completely made of carbon fiber, and has free-floating movements which enable a view of the entire anatomy.

1464 NW 82nd Ave. – Doral, FL – 33126
www.klyomedical.com – sales@klyomedical.com
Tel. 1 (305) 330-5025

* Due to technical advances KLYO Medical Systems, INC., reserves the right to modify technical specifications without prior notice.

*The images shown are only for demonstrative purposes.

DS 007-01-6/29/2018



TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table, Model KL-RX1

Technical Data		KLRX1
Movements		Electro motorized
Electrical control		Microprocessors
Transfer		5" antistatic wheels (127 mm)
Brake system		Motorized
Remote Control		Yes
Infrared Control		Yes, Optional
Column Control		Yes
Joystick Control		Yes
Electro-motorized Movements	Column elevation and descent	30.32" – 38.19" (770mm – 970mm)
	Transversal shift	12.60" (320mm)
	Longitudinal displacement	22.44" (570 mm)
	Trendelenburg	20° ± 1°
	Reverse Trendelenburg	20° ± 1°
	Left Tilt	15° ± 1°
	Right Tilt	15° ± 1°
Automatic return to "0" position		Yes
Patient orientation selection		No
Emergency function for control failure		Yes, in column control, to activate all movements

Physical Data		KLRX1
Maximum patient weight centered at base		882 lbs (400 Kg)
Maximum patient weight with displaced tabletop		330 lbs (150 Kg)
Base		Stainless steel
Base cover material		ABS or Stainless steel
Column		Stainless steel
Surface structure		Stainless steel
Side rails		Stainless steel
Table Top	Material	Carbon fiber, completely radiolucent
	Number of sections	2 ▪ Head plate ▪ Table Top
Length		94.49" (2400 mm)
Width (including side rails)		23.62" (600 mm)
Pads	Material	Viscoelastic, removable, independent, antistatic, seamless
	Thickness	2" (50.08 mm) optional 3" (76.20 mm)
	Radiolucent	yes

1464 NW 82nd Ave. – Doral, FL – 33126
www.klyomedical.com – sales@klyomedical.com
 Tel. 1 (305) 330-5025

* Due to technical advances KLYO Medical Systems, INC., reserves the right to modify technical specifications without prior notice.


*The images shown are only for demonstrative purposes.

DS 007-01-6/29/2018

TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table, Model KL-RX1

Electrical Data		KLRX1
Voltage		90 – 130 V
Frequency		60 Hz
Liquid protection rating		IPX 4
Protection scale against electrical currents		Type B
Rechargeable batteries	Autonomy	160 hours
	Charge indicator	Yes
	Time for full battery charge	12 hours



ISO 9001:2015 Certified

ISO 13485: 2016

EN ISO 13485:2016 Certified

FDA Registered

1464 NW 82nd Ave. – Doral, FL – 33126
www.klyomedical.com – sales@klyomedical.com
 Tel. 1 (305) 330-5025

* Due to technical advances KLYO Medical Systems, INC., reserves the right to modify technical specifications without prior notice.

*The images shown are only for demonstrative purposes.