

TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table

Model KL500



The KLYO MEDICAL SYSTEMS, INC. Surgical tables are designed to support loads of up to 465Kg (1025.15 Lbs) in the electro-motorized model KL500. All movements are smooth and silent, offering an electric longitudinal displacement of 340mm (13.38") towards the head, facilitating the placement of imaging equipment (C-Arm or fluoroscope). The KL500 table is radiolucent in all its sections.

1464 NW 82nd Ave. – Doral, FL – 33126
www.klyomedical.com – sales@klyomedical.com
Tel. 1 (305) 330-5025

* Due to technical advances KLYO Medical Systems, INC., reserves the right to modify technical specifications without prior notice.

*The images shown are only for demonstrative purposes.

DS 005-05 - 08/12/2024

TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table

Model KL500

Technical Data		KL500
Movements		Electro-motorized
Electronic control		Microprocessors
Transport		125mm (5") anti-static wheels
Brake system		Motorized
Mechanical movements	Headrest Detachable	Continuously adjustable +45°/-90°
	Lumbar region elevator	110mm (4"), optional
Electro-hydraulic movements	Column elevation and descent	700mm – 1000mm (27.56" – 39.37")
	Leg sections Independent and detachable	Adjustable continuously: UP: +11° ± 2° DOWN: -90° ± 2° Scissor movement: 0° a 180°
	Fowler position (Continuous backrest movement)	UP: +71° ± 2° DOWN: -37° ± 2°
	Longitudinal displacement	340mm (13.38")
	Trendelenburg	30° ± 1°
	Reverse Trendelenburg	30° ± 1°
	Left lateral tilt	20° ± 2°
	Right lateral tilt	20° ± 2°
	Flex - Reflex	217° ± 4° 109° ± 4°
Control	Remote control	Yes
	Infrared control	Yes, optional
	Column control	Yes
Automatic table return to "0" position		Yes
Patient orientation selection		Yes, by control.
Emergency function in case of remote-control failure		Yes, in the column control to activate all movements.

TECHNICAL DATA

KLYO MEDICAL SYSTEMS, INC., Surgical Table

Model KL500

Physical data		KL500
Load capacity		465Kg (1025.15 lbs.)
Base		Stainless steel
Base cover		Highly resistant ABS to mechanical stress or Stainless steel
Column		Stainless steel
Surface structure		Stainless steel
Side rails		Stainless steel
Tabletop	Material	Phenolic. Totally radiolucent
	Sections	5 to 7 ▪ Headrest ▪ Leg sections (Left / Right) ▪ Pelvis ▪ Kidney elevator ▪ Lower back ▪ Upper back
Overall length		2170mm (85.43")
Tabletop width (including side rails)		600mm (23.62")
Cushions	Material	Viscoelastic, removable, independent (one for each section of the tabletop), antistatic, seamless for easy cleaning
	Thickness	50.08mm (2"), optional 76.20 (3")
	Radiolucency	Yes

Electrical specifications		KL500
Input power supply		100 – 240 AC / 4 – 2 A
Input frequency		50/60 Hz
Mains fuse – normal		3A / 250 V
Maximum input power consumption		350 VA
Degree of protection against liquids		IPX 4
Protection scala against electric currents		Type B
Rechargeable batteries	Autonomy	200 procedures or 3 weeks
	Charge indicator	Yes
	Voltage	24 V (2 of 12 V / 5 Ah)
	Charging time to full capacity	12 hours

QUALITY
CERTIFICATIONS
(Amtivo (USA) Inc.):

ISO 9001: 2015 QUALITY
MANAGEMENT SYSTEM

ISO 13485: 2016 MEDICAL
DEVICE QUALITY
MANAGEMENT SYSTEM

PRODUCT CERTIFICATIONS:

IEC 60601-1

IEC 60601-1-2

IEC 60601-1-4

IEC 60601-2-46

REGISTRATIONS:

FDA

1464 NW 82nd Ave. – Doral, FL – 33126
www.klyomedical.com – sales@klyomedical.com
Tel. 1 (305) 330-5025

* Due to technical advances KLYO Medical Systems, INC., reserves the right to modify technical specifications without prior notice.

*The images shown are only for demonstrative purposes.

DS 005-05 - 08/12/2024